



Article No.	ADS39
Coating Material	Nitrile
Coating Color	Blue/Black
Liner	UHMWPE
Liner Color	White
Finishing	Flat/Sandy
Cuff style	Gauntlet
Gauge	18
Size	8,9,10,11,12

PERFORMANCE

- EN374-1:2016 Type A certified
- Superb cut protection of ISO13997 level D
- Excellent resistance against chemicals, oils, acids etc.
- Unique coating formulation technology contributing to extra softness, comfort, durability and dexterity
- Sandy finish guaranteeing super grip in particular to oil and wet working condition

APPLICATION

- Assembly in chemical, grease and oils condition
- Maintenance
- Offshore petroleum
- Chemical handling
- Oil & Petrol Refining

www.fortessafety.com

info@fortessafety.com






Tel. +86 2157832572

Fax. +86 2157832892

Version 2018

FORTES

CERTIFICATION

EN388  4X43D	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	EN ISO 374-1:2016/Type A  AJKLOT	EN374-5 	
	TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4			
	ISO 13997 A B C D E F				
EN407  X1XXXX	FLAMMABILITY 0 1 2 3 4			CONTACT HEAT 0 1 2 3 4	
	CONVECTIVE HEAT 0 1 2 3 4			RADIANT HEAT 0 1 2 3 4	
	SMALL SPLASHES OF MOLTEN METAL 0 1 2 3 4			LARGE SPLASHES OF MOLTEN METAL 0 1 2 3 4	

For more information, please visit [here](#)

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	10.50	11.00	11.50	12.00	12.5
Length	30cm				

PACKING

Poly bag	6 pairs per polybag with 1 consumer information sheet
Carton	10 polybags of 60 pairs per carton

GLOVE CARE

Laundering	Rinse the gloves in running water (less than 40° C) before removing, using a neutral detergent if necessary
Storage	Store the gloves in their original packaging protected from humidity

RECOMMENDATION FOR USE

- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm
- Do not use in cases of electrical or critical thermal risk

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2018

FORTES