Level F Cut Protective Glove with Sandy Nitrile



Article No.	AN6S
Coating Material	Nitrile
Coating Color	Black
Liner	UHMWPE / Steel
Liner Color	Blue
Finishing	Sandy
Cuff Style	Knit wrist
Gauge	13
Size	7,8,9,10,11,12

PERFORMANCE

- ISO 13997 TDM cut level F and ANSI cut level A6 certified
- 10-finger touchscreen functionary enables you to use all touch screen devices on the job
- Advanced yarns technology contributes to high cut protection but still very soft, flexible and comfortable, no steel wire would be felt and touched
- Excellent resistance to oil and acids in dry and wet environments
- Super grip in both dry and oily working conditions
- Ideal for heavy duty work and critical cut/blade hazards

APPLICATION

- Automotive industry
- Glass industry
- Paper industry
- Blades manufacturing
- Machinery and equipment maintenance

www.fortessafety.com info@fortessafety.com Tel. +86 2157832572 Fax. +86 2157832892 Version 2021



CERTIFICATION

EN388	ABRASION 0 1 2 3 4 TEARING 0 1 2 3 4 ISO 13997 A B C D E F	CUTTING 0 1 2 3 4 5 PUNCTURE 0 1 2 3 4	ANSI A6 CUT	R	Santliged Actifient	OEKO-TEX® COMMONIC IN TETTUS STANDARD 100 SH020 ISSISS TETEX	
EN407	FLAMMABILI	ТҮ		CONT	ACT HEAT		
$\left(\frac{5}{5} \right)$	0 1 2 3 4 CONVECTIVE	HEAT		0 1 2 RADI/	3 4 ANT HEAT		
	01234 SMALL SPLA	SHES OF MOL		012	-	S OF MOLTEN METAL	
X1XXXX	01234			0 1 2			
For more information	ation, please visit <u>he</u>	ere		012			

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(7) Small	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	9.00	9.50	10.00	10.50	11.00	11.50
Length	23.00	24.00	25.00	26.00	27.00	28.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

It is cut resistant glove not cut proof, do not use them next to moving machinery.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

