Cut Protective Glove with Sandy Nitrile



Article No.	BN5S
Coating Material	Nitrile
Coating Color	Black
Liner	UHMWPE/Glass
Liner Color	Hi-Vis Yellow
Finishing	Sandy
Cuff Style	Knit wrist
Gauge	13
Size	6,7,8,9,10,11,12

PERFORMANCE

- ISO 13997 Cut level C glove with excellent abrasion resistance
- Sandy surface offers excellent grip, particularly to slippery object handling
- Excellent flexibility and dexterity minimizing hand fatigue
- 360° breathability to keep your hands cool full day
- Washable for up to 12 times and cut level remains
- Excellent heat resistance

APPLICATION

- Automobile
- Glass industry
- Construction
- Logistics and Warehousing
- Handling of ceramics, metal sheets, plastic injection moulds etc.

www.fortessafety.com info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES

CERTIFICATION

EN388	ABRASION 0 1 2 3 4 TEARING 0 1 2 3 4 ISO 13997 A B C D E F	CUTTING 0 1 2 3 4 5 PUNCTURE 0 1 2 3 4	ANSI A3 CUT	Santliged: Actifrest	OEKO-TEX® COMPOSENCE IN TEXTILIS STANDARD 100 SH020 153533 TESTEX	i	
EN407	FLAMMABIL	ІТ		со	NTACT HEAT		
	0 1 2 3 4			0 1 2 3 4			
\bigcirc	CONVECTIVE HEAT			RADIANT HEAT			
X1XXXX	01234			0	1234		
SMALL SPLASHES OF MOLTEN		TEN METAL	TEN METAL LARGE SPLASHES OF MOLTEN METAL				
	01234			0	1234		

For more information, please visit here

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(6) X Small	(7) Small	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	8.50	9.00	9.50	10.00	10.50	11.00	11.50
Length	22.00	23.00	24.00	25.00	26.00	27.00	28.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

- It is cut resistant glove not cut proof, do not use them next to moving machinery.
- Do not use in cases of chemical, electrical or thermal risk.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

