

Reinforced Crotch 13gg Cut Glove with Double dip Nitrile

DS3GX



Article No.	DS3GX
Coating Material	Nitrile
Coating Color	Green/Black
Liner	UHMWPE
Liner Color	Salt/Pepper
Finishing	Flat/Sandy
Cuff Style	Knit wrist
Gauge	13
Size	7,8,9,10,11,12
Reinforcement	Nitrile

PERFORMANCE

- ISO 13997 TDM Cut level B certified
- First flat soft nitrile dip contributing resistance to liquid and Second sandy surface offering excellent grip in both dry and wet working conditions, in particular to slippery object handling
- Excellent flexibility and dexterity minimizing hand fatigue
- The reinforcement greatly extends glove life to save your cost and provides extra protection in the most weak area
- Great heat resistance
- Available in 3/4 dip for 1st layer and palm dip for 2nd layer (DS43X)

APPLICATION

- Automobile
- Glass industry
- Recycling industry
- Machinery and equipment maintenance

www.fortessafety.com

info@fortessafety.com







Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES

CERTIFICATION

EN388  4X43B	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	ANSI  A2			
	TEARING 0 1 2 3 4	PUNCTURE 0 1 2 3 4	CUT			
	ISO 13997 A B C D E F					
EN407  X1XXXX	FLAMMABILITY 0 1 2 3 4				CONTACT HEAT 0 1 2 3 4	
	CONVECTIVE HEAT 0 1 2 3 4				RADIANT HEAT 0 1 2 3 4	
	SMALL SPLASHES OF MOLTEN 0 1 2 3 4				LARGE SPLASHES OF MOLTEN METAL 0 1 2 3 4	

For more information, please visit [here](#)

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(7) Small	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	9.00	9.50	10.00	10.50	11.00	11.50
Length	23.00	24.00	25.00	26.00	27.00	28.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs per carton

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

- It is cut resistant glove not cut proof, do not use them next to moving machinery.
- Do not use in cases of chemical, electrical or thermal risk.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES