Reinforced Crotch Cut Glove with Double Dip Nitrile



Article No.	DS45X
Coating Material	Nitrile
Coating Color	Blue/Black
Liner	UHMWPE/Glass
Liner Color	Salt /Pepper
Finishing	Flat/Sandy
Cuff Style	Knit wrist
Gauge	13
Size	7,8,9,10,11,12
Reinforcement	Nitrile

PERFORMANCE

- Excellent resistance to Oil and Water
- ISO 13997 Cut level D glove with excellent abrasion resistance
- Excellent flexibility and dexterity minimizing hand fatigue
- The reinforcement greatly extends glove life to save your cost and provides extra protection in the most weak area
- First flat soft nitrile dip contributing resistance to liquid and Second sandy surface offering excellent grip in both dry and wet working conditions, in particular to slippery object handling
- Great heat protection

APPLICATION

- Automobile
- Glass industry
- Recycling industry
- Machinery and equipment maintenance

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021



CERTIFICATION

EN388

ABRASION CUTTING

G

01234

012345







4X43D

X1XXXX

TEARING 0 1 2 3 **4**

PUNCTURE 0 1 2 **3** 4

CUT

ISO 13997

ABCDEF

EN407 FLAMMABILITY

CONTACT HEAT

01234

0 1 2 3 4

CONVECTIVE HEAT

RADIANT HEAT

01234 01234

SMALL SPLASHES OF MOLTEN METAL LARGE SPLASHES OF MOLTEN METAL

01234 01234

For more information, please visit here

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(7) Small	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	9.00	9.50	10.00	10.50	11.00	11.50
Length	23.00	24.00	25.00	26.00	27.00	28.00

PACKING

Poly bag	12 pairs with 1 consumer information sheet
Carton	120 pairs per carton

GLOVE CARE

Laundering	Wash at 40°C max and machine washing available.
Storage	Store the gloves in their original packaging protected from heat, light and humidity.

RECOMMENDATION FOR USE

- It is cut resistant glove not cut proof, do not use them next to moving machinery.
- Do not use in cases of chemical, electrical or thermal risk.

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

