



Article No.	ADS39
Coating Material	Nitrile
Coating Color	Blue/Black
Liner	UHMWPE
Liner Color	White
Finishing	Flat/Sandy
Cuff style	Gauntlet
Gauge	18
Size	8,9,10,11,12

PERFORMANCE

- Waterproof & Oil repellent
- EN ISO 374-1:2016/Type A certified
- Superb cut protection of ISO13997 level D certified (18 gauge knit)
- Excellent resistance against chemicals, oils, grease, acids etc.
- 18 gauge knit ensuring the glove with extra softness, comfort and dexterity
- Micro-foam with sandy finish guaranteeing super grip in particular to oil and wet working conditions
- OEKO-TEX Standard 100 certified

APPLICATION

- Mining
- Offshore petroleum
- Chemical handling
- Oil & Gas industry
- Fishery Industry
- Assembly in chemical, grease and oils conditions

www.fortessafety.com

info@fortessafety.com








Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES

CERTIFICATION

EN388  4X43D	ABRASION 0 1 2 3 4	CUTTING 0 1 2 3 4 5	ANSI  A4 CUT	EN ISO 374-1:2016/Type A  AJKLOT	EN374-5 	EN1149  
EN407  X1XXXX	BURNING BEHAVIOUR 0 1 2 3 4	CONVECTIVE HEAT 0 1 2 3 4		CONTACT HEAT 0 1 2 3 4	RADIANT HEAT 0 1 2 3 4	
	SMALL SPLASHES OF MOLTEN METAL 0 1 2 3 4			LARGE SPLASHES OF MOLTEN METAL 0 1 2 3 4		

For more information, please visit [here](#)

DIMENSIONS (+/- 0.50 cm)

Sizes Available	(8) Medium	(9) Large	(10) X Large	(11) 2X Large	(12) 3X Large
Palm Width	10.50	11.00	11.50	12.00	12.50
Length	32cm				

PACKING

Poly bag	6 pairs per polybag with 1 consumer information sheet
Carton	60 pairs per carton

GLOVE CARE

Laundering	Rinse the gloves in running water (less than 40° C) before removing, using a neutral detergent if necessary
Storage	Store the gloves in their original packaging protected from humidity

RECOMMENDATION FOR USE

- Turn the cuff end down in order to prevent a hazardous chemical from dripping onto the arm
- Do not use in cases of electrical or critical thermal risk

www.fortessafety.com

info@fortessafety.com

Tel. +86 2157832572

Fax. +86 2157832892

Version 2021

FORTES